

Technical Data Sheet (TDS)







2K VEPOXY SP GOLD

(TILE EPOXY GROUT 2K)

Product Description:

2K VEPOXY SP GOLD is a two component specially formulated chemical resistant grout for heavy duty applications. It is recommended for areas where hygiene is of utmost importance.

Areas of Application:

- Indoor and outdoor grouting of ceramic tile and natural stone floors and walls.
- Suitable for acid-resistant bonding and rapid setting of ceramic tiles, Institutional Kitchens, Schools, Swimming pools, Rest rooms, Hotels & Restaurants etc.



Date/Revised: 27-03-2021

Application:

1. Surface Preparation:

- ❖ Before starting the work, remove the spacers placed between the tiles.
- Scratch between the tile joints and clean the joints, remove the dust and dirt using sponge.
- ❖ Make sure that the working temperature should be between 15°C 30°C.

2. Mixing:

- Transfer the entire bottles of VEPOXY Component A & Component B to a clean mixing pail and mix well until a smooth paste is obtained.
- For perfect mixing and avoiding overheating of the mixture, which could reduce working time, a low speed electric stirrer should be used.
- Use the paste within 45 minutes from mixing.

3. Application:

- Immediately pour entire quantity from the mixing pail on to working area
- Use a plastic sheet as a drop cloth
- Fill the grout joins using standard epoxy grouting techniques
- ❖ Ensure the grout joints are fully packed with 2K VEPOXY SP GOLD material
- Remove the excess material as much as possible before initial cleaning with grouting rubber float
- Do not leave excess material on the faces of the tiles

Advantages:



Technical Data Sheet (TDS)







- ❖ For tile joints having flesh joint from 0-6 mm
- ❖ Anti-Fungal & Anti-Bacterial
- Stain free
- **t** Easy to apply and clean
- Non-Shrinkage, Non-Cracking and Non-Powdering
- Clings well to the vertical surfaces
- Water cleanable when fresh

Packaging:

❖ 2 kg - Pail & 5 kg - Pail

Shelf Life:

Shelf life is 24 months from the date of manufacturing. Store at cool & dry place, away from moisture.

COLOURS:

2K VEPOXY SP GOLD is available in 22 colours from the "VBOND Coloured Grouts" range.

Technical Data:

S.NO	PROPERTIES	Results
1	Mix Ratio	Comp A : Comp B = 9: 1
2	Open time	30 Minutes
3	Pot Life	45 Minutes
4	Flexural Strength	30 (N/mm2)
5	Water absorption	0.05 g
6	Thermal Shock	24 (N/mm2)
7	Sag	No Sag
8	Compressive strength	55 (N/mm2)

Precautions & Limitations:

- During cold whether protect the finished work from the traffic until it fully cured
- ❖ 2K VEPOXY SP GOLD may irritate eyes and skin.
- ❖ Avoid to contact with eyes and prolonged time with skin.
- In case of contact flush with plenty of water thoroughly



Technical Data Sheet (TDS)







- Don't take internally, silica sand may cause for cancer
- Keep away to reach children

Other Product Categories available with VBOND as below

- ❖ VB-Ready Plaster
- Block Jointing Mortar
- Premium Tile Adhesives
- Epoxy Grouts & Unsanded Grouts
- Water Proofing Products
- Micro Concrete and Repair Product
- Industrial/Precision Grout and Anchors
- Epoxy Flooring
- Self-level Epoxy Flooring
- Floor Screeds

Technical Services

Technical assistance information is available by calling the VBOND Technical Service at **+91 96664 96664** or mail us at sales@valuebond.in

Address:

VALUE PACK INDIA PRIVATE LIMITED

(AN ISO 9001-2015 CERTIFIED COMPANY)

Regd Office: Unit G4, Ground Floor

Plot No. 7-6-43/1, SV Landmark, Bollaram Road Medchal,

Hyderabad, Telangana-500090.

Corp Office: Plot No. 217/A,

Near Metro Station, Calvary Temple Road, Miyapur,

Hyderabad, Telangana-500049

Factory: Sy. No. 210 & 211, Near A.P. Met IDA Bollaram, Sangareddy, Telangana-502 325.

Website: www.valuebond.in

CIN NO: U74999TG2014PTC095270

Customer Care

Phone: +91 96664 96664, Email: sales@valuebond.in